

Features

- Single 24 position easy to use rotary switch
- High sensitivity of 100uV
- Automatic polarity indication on DC range
- All ranges are protected
- Diode testing with 1mA fixed current
- Transistor hFE test
- Audible Continuity Test Facility
- 500V AC/DC Protection in Resistance, Continuity and Diode Test Range in Red Colour.

General Specifications

Maximum display : 1999 counts (3 1/2 digits) with Automatic Polarity Indication.
 Indication method : LCD display
 Measuring Method : Dual-slope integration A-D converter system
 Overrange Indication : "1" Figure only in the display
 Maximum Common Mode Voltage : 500V DC/AC rms
 Reading Rate : 2-3 Reading per sec (approximate)
 Temperature for Guaranteed Accuracy : 23°C±5°C
 Temperature Ranges : Operating 0°Cto40°C, 32°F to 104°F
 Storage 10°C to 50°C, 14°F to 122°F
 Power Supply : One 9-volt battery (NEDA 1604, 6F22 type or equivalent)
 Lower Battery indication : "BAT" to left of display
 Size : 85(w) X 165(D) X 32(H)mm
 Weight : 250g (including 9 Volt battery)
 Accessories : Operating manual, set of test leads, holster and carrying case.



Technical Specifications

Accuracies are ± (% reading + No. of digits) Guaranteed for 1 year, 23°C±5°C, less than 75%RH

DC Voltage

Range	Accuracy	Resolution
200mV	+0.5% + 1	100uV
2V		1mV
20V		10mV
200V	+0.8% + 2	100mV
1000V		1V

Input impedance: 10M ohm on all ranges.

Overload protection: 250Vrms on 200mV range & 1000V DC or peak AC on all other ranges.

AC Voltage

Range	Accuracy	Resolution
2V	± 0.8% ± 3	1mV
20V		10mV
200V		100mV
750V	± 1.2% ± 3	1V

Input Impedance: 10M ohm on all ranges.

Note: Specifications are subject to change.

Frequency

Range : 40Hz to 400Hz

Overload protection : 50Vrms or 1000V peak continuous on all ranges

Indication : Average (rms of sine wave)

DC Current

Range	Accuracy	Resolution
200uA	± 0.8% ± 1	0.1uA
2mA		1uA
20mA	± 1.2% ± 1	10uA
200mA		100uA
20A		10mA

Overload

Protection : 0.2A/250V fuse (20A range not fused)

Maximum

Input Current : 20A, 15 sec.

AC current

Range	Accuracy	Resolution
2mA	± 1.2% ± 3	1uA
20mA		10uA
200mA	± 2% ± 3	100uA
20A		10mA

Overload

Protection : 0.2A/250V fuse (20A range not fused)

Frequency

Range : 40Hz to 400Hz

Maximum

Input Current : 20A 15 sec.

Indication : Average (rms of sine wave)

Resistance

Range	Accuracy	Resolution
200	± 0.8% ± 3	0.1
2K		1
20 K		10
200 k	± 0.8% ± 1	100
2 M		1K
20 M		10k

Overload

Protection: 500V DC/rms AC

Tesca Technologies Pvt. Ltd.

IT-2013, Ramchandrapura Industrial Area, Sitapura Extension,
 Near Bombay Hospital, Vidhani Circle, Jaipur-302022, Rajasthan, India,
 Tel: +91-141-2771791 / 2771792; Email: info@tesca.in, tesca.technologies@gmail.com
 Website: www.tesca.in