




Technical Specification

Function	Range	Resolution	Accurate	Memo
DCV	200mV	100μV	±(0.5%+3)	Max.1000V
	2000mV	1mV		
	20V	10mV		
	200V	100Mv		
	1000V	1V	±(0.8%+5)	
ACV	200V	100mV	±(1.2%+8)	Max.750V
	750V	1V		
DCA	200μA	100μA	±(1.0%+5)	Max.200mA
	2000μV	1μV		
	20mA	10μA		
	200mA	100μA	±(1.2%+8)	
	10A	10mA	±(2.0%+8)	
Resistance	200	0.1	±(1.0%+8)	Maximum Open circuit voltage 3.0V
	2000	1	±(1.0%+2)	
	20K	10		
	200K	100		
	2000K	1K		
Diode			Test current 1.5mA	
hFE	NPN PNP	0 1000	Vce 2.8V Ib 10μA	
Temp.	-10°C-1000°C	1°C	±(3%+3°C)	
Buzzer	Built in Buzzer sounds if resistance is less than 30-200			

Note: Specifications are subject to change.

Tesca Technologies Pvt. Ltd.

IT-2013, Ramchandrapura Industrial Area, Sitapura Extension,
Near Bombay Hospital, Vidhani Circle, Jaipur-302022, Rajasthan, India,
Tel: +91-141-2771791 / 2771792; Email: info@tesca.in, tesca.technologies@gmail.com
Website: www.tesca.in